Quick Start Guide
4/8-CH DVR

1. Install Hard Drive &DVD Writer

1.1 Install Hard Drive

***Notice**: 1. this series support one SATA hard drives. Please use the hard drive the manufacturers recommend specially for security and safe field.*

2. Please calculate HDD capacity according to the recording setting. Please refer to "Appendix B Calculate Recording Capacity".

Step1: Unscrew and Open the top cover

Step2: Connect the power and data cables. Place the HDD onto the bottom case as below.

Fig 1.1 Connect HDD

Step3: Screw the HDD as below.

Note: For the convenience to install, please connect the power and data cables firstly, and then screw to fix.

Fig 1.2 Screw HDD

2. Connections

2.1 Rear view for 4-ch DVR



Fig 2.1 Rear view for 4-ch DVR

1	4 CH Audio input	2	Video input channels from 1-4
3	Audio output, connect to the sound box	4	Connect to monitor
5	Connect to speed dome	6	Connect to keyboard
7	1-ch relay output. Connect to external alarm	8	+5 V and Grounding
9	Connect to external sensor1-4	10	Spot out: Connect to monitor as an AUX output channel by channel. Only video display, no menu show
11	VGA output, connect to monitor	12	Network port
13	Connect USB mouse or connect external USB devices	14	POWER INPUT

2.2 Rear view for 8-ch DVR



Fig 2.2 Rear view for 8-ch DVR

1	4 CH Audio input	2	Video input channels from 1-8
3	Audio output, connect to the sound box	4	Connect to monitor
5	Connect to speed dome	6	Connect to keyboard
7	1-ch relay output. Connect to external alarm	8	+5 V and Grounding
9	Connect to external sensor1-8	10	Spot out: Connect to monitor as an AUX output channel by channel. Only video display, no menu show
11	VGA output, connect to monitor	12	Network port
13	Connect USB mouse or connect external USB devices	14	POWER INPUT

3. Power on

Step1: connect with the source power; switch on the power button near the power port in the rear panel

Step2: the device will be loaded, and the power indicator will display blue

Step3: before start, a WIZZARD window will be pop-up and show some information about time zone，time setup，network configuration, record configuration and disk management. User can setup here and refer to the concrete setup steps from the corresponding chapters. If users don't want to

setup Wizard, please click Exit button to exit.

After the device power on, if there is no menu or only has live image display, user can long press ESC button to switch.

Notice: this serial device can only display menu on VGA monitor or BNC monitor at one time, if there is live image display without menu display, please check up whether other device has menu display firstly, or long press ESC key to wait for login dialog box to appear. Long press ESC key can switch the output between BNC and VGA.

4. Basic setup

4.1 Accessing the DVR menus

4.1.1 Login

Press the MENU button which will bring the LOGIN dialogue box and enter the user name: admin and password: 123456

Fig 4.1 Login

4.1.2 Main menu setup

Click right mouse, or press ENTER button on the front panel can enter into the main menu. Menu-System refer to Fig 4.2



Fig 4-2 Main menu setup

Basic configuration: user can set video system, menu language, audio, time and authorization check.

Live configuration：User can set name/time display, picture color and hide cameras.

Record configuration：User can set record quality, frame rate, resolution, time stamp and recycle.

Schedule configuration: users can set schedule for timer, motion detection, and sensor alarm respectively.

Alarm configuration: users can set sensor type, alarm trigger and buzzer alarm.

Network configuration: Users enable network function, and configure IP address, DDNS, transmission video parameters here.

User configuration: Administrator can add, delete users, and change their authorization

PTZ configuration: users can set protocol, baud rate, address, presets and auto cruise track here.

Reset configuration: users can reboot the device.

4.2 DVR recording modes

User need to install and format a HDD, and set all the recording parameters before recording. There are four kinds of record modes.

4.2.1 Manual Recording

User can press REC button on the front panel after quitting system setup. Press this button again to stop recording.

Or press REC button on remote controller, click again to stop.

Or click REC button on the tool bar with mouse, click again to stop.

4.2.2 Schedule Recording

Enter into main menu—schedule configuration (refer to Fig 4-3). Users can set different schedule time for every day in one week. If user wants a special schedule for one day can use Holiday function.

The column means the seven days of a week from Monday to Sunday, the row means 24 hours of a day. Click the grid to do relevant setup. Blue means checked area, gray means unchecked area.



Fig 4-3 Schedule record setup

4.2.3 Motion Detection Recording

Motion detection recording: when there is a motion event detected, the camera will be triggered to record and have an alarm out.

Enter into main menu-motion configuration (refer to Fig 4-4), enable Detection first;



Fig 4-4 Motion detection interface

Enter Motion detection area (refer to Fig 4-5) to set Sensitivity and Detection area.

Fig 4-5 motion detection area setup

4.2.4 Alarm Recording

Enter into main menu-Alarm configuration (refer to Fig 4-6), enable Detection first, setup the device type.

Fig 4-6 sensor alarm record

Enter into Trigger configuration, select alarm out and recording cameras and linked PTZ; set Alarm out hold time and Buzzer hold time. Click OK to save settings.

4.3 Playback

This unit supports live record playback, time search and event search. It displays full or 4 screens in playback.

4.3.1 Live playback

Click Play button to playback the record. Refer to Figure4-7. User can do concrete operation by click the buttons on screen.



Fig 4-7 live playback

4.3.2 Time search

Enter into Search configuration, select Time search. If it recorded in a certain day, the date will show highlight.



Fig 4-8 time search

Select a date, press Search button, click the time grid to set the play start time or input play record time manually. The selected time match the blue grid.

Click Play button. It will play from the time point where user set.
Click the relative buttons on the screen to do fast forward/rewind, pause, stop, and change the screen mode and re-search.

4.3.3 Event search

Enter into Search configuration, select Event search (refer to Fig 4-9), and choose a certain day in the event search interface.



Fig 4-9 Event search

Click Search button, the searched event information will displayed in the event list box, user can select date, channel, tick off Motion, Sensor or All accordingly.
Double click a video file to playback.

4.4 Back up

This unit supports backup by USB mobile storage device.



Fig 4-10 Backup setup

Install USB mobile storage device, enter into Backup interface), set the start & end time, select channels, click Search button; the searched data will be displayed in the data backup list box.

5. Remote Surveillance

To making remote access, the DVR should be connecting to LAN or Internet. There are three kind of method for remote accessing.

5.1 Using DHCP to get IP address automatically

Click the Menu button, enter into System—Network configuration (refer to Fig 5-1), enable DHCP in the both the DVR and the router.



Fig 5-1 Network configuration

Enter Video to set network video parameters like resolution, frame rate etc.
Open an IE browser on computer on the same LAN. Input the IP address of the DVR in IE address blank and enter.
IE will download ActiveX automatically. Then a window pops up and asks for user name and password.
Input name and password correctly (the default user name is admin and the password is 123456), and enter. It will show the remote picture.
Note：If the ActiveX cannot be downloaded or installed, please refer to Appendix A Q7 in the user manual.

5.2 Access DVR on WAN

Input IP address, Subnet, Gateway. If using DHCP, please enable DHCP in both the DVR and router.
Enter Video to set network video parameters like resolution, frame rate etc.
Forward IP address and port number in Virtual Server setup of the router or virtual server. Close firewall.
If users want to utilize dynamic domain name, need apply for a domain name in a DNS server supported by the DVR or router. Then add to the DVR or router.

Open IE browser, input IP address, or dynamic domain name and enter. If HTTP port is not 80, add the port number after IP address or domain name.
IE will download ActiveX automatically. Then a window pops up and asks for user name and password.
Input name and password correctly, and enter to view.

5.3 Connect the DVR to Internet through dial-up ADSL

Input IP address, Subnet, Gateway gotten from your ISP. If using ADSL, please input user name and password, and click OK. The DVR will connect the server and show “connection succeeds”.
The following steps are the same as STEP4-7 of the connection way above.
If users want to utilize dynamic domain name, need apply for a domain name in a DDNS server supported by the DVR or router. Then add to the DVR or router.
Open IE browser, input IP address, or dynamic domain name and enter. If HTTP port is not 80, add the port number after IP address or domain name.
IE will download ActiveX automatically. Then a window pops up and asks for user name and password.
Input name and password correctly, and enter to view.